

WHAT IS CLAIMED IS:

5

1. A resonance-frequency measuring method for measuring a resonance frequency of an information recording/reproducing device reproducing information recorded on a medium by driving a mechanism unit, the method comprising:

10 the measuring step of applying sine-wave oscillations at different frequencies one by one to said mechanism unit, and counting the number of times information reproduced upon application of each of said sine-wave oscillations differs from information indicating an aimed location; and

15 the resonance-frequency determining step of determining said resonance frequency according to said number of times counted in said measuring step.

20

2. The resonance-frequency measuring method as claimed in claim 1, wherein said measuring step applies said sine-wave oscillations to said mechanism unit by adding sine-wave signals at different frequencies one by one to a control signal controlling an actuator to drive said mechanism unit.

30

3. The resonance-frequency measuring method as claimed in claim 1, wherein said resonance-frequency determining step judges a frequency of the sine-wave oscillation maximizing

35

said number of times to be said resonance frequency.

5  
4. The resonance-frequency measuring method as claimed in claim 2, wherein said resonance-frequency determining step judges a frequency of the sine-wave signal maximizing said  
10 number of times to be said resonance frequency.

15 5. An information recording/reproducing device comprising:  
a mechanism unit causing information recorded on a medium to be tracked;  
a driving unit driving said mechanism  
20 unit;  
a filter removing an unnecessary component from a control signal controlling said driving unit;  
measuring means for applying sine-wave oscillations at different frequencies one by one to  
25 said mechanism unit, and counting the number of times information reproduced upon application of each of said sine-wave oscillations differs from information indicating an aimed location;  
resonance-frequency determining means for  
30 determining said resonance frequency according to said number of times counted by said measuring means; and  
filter adjusting means for adjusting a characteristic of said filter so that said resonance  
35 frequency determined by said resonance-frequency determining means becomes a cutoff frequency of said filter.

6. The information recording/reproducing device as claimed in claim 5, wherein said measuring means applies said sine-wave oscillations to said mechanism unit by adding sine-wave signals at  
5 different frequencies one by one to said control signal.

10

7. The information recording/reproducing device as claimed in claim 5, wherein said resonance-frequency determining means judges a frequency of the sine-wave oscillation maximizing  
15 said number of times to be said resonance frequency.

20

8. The information recording/reproducing device as claimed in claim 6, wherein said resonance-frequency determining means judges a frequency of the sine-wave signal maximizing said number of times to be said resonance frequency.

25

9. The information recording/reproducing device as claimed in claim 5, wherein said filter comprises a plurality of notch filters combined so as to have a predetermined notch filter characteristic.

30  
35

10. The information recording/reproducing device as claimed in claim 9, wherein said filter comprises:

5 a first notch filter having a first cutoff frequency and exhibiting substantially symmetrical gain changes at frequencies below and above said first cutoff frequency;

10 a second notch filter having a second cutoff frequency lower than said first cutoff frequency, and exhibiting a smaller amount of gain changes and a smaller maximum gain at frequencies below said second cutoff frequency than an amount of gain changes and a maximum gain at frequencies above said second cutoff frequency; and

15 a third notch filter having a third cutoff frequency higher than said first cutoff frequency, and exhibiting a larger amount of gain changes and a larger maximum gain at frequencies below said third cutoff frequency than an amount of gain changes and  
20 a maximum gain at frequencies above said third cutoff frequency.

25

11. The information recording/reproducing device as claimed in claim 10, wherein said filter further comprises a fourth notch filter having a  
30 fourth cutoff frequency lower than said second cutoff frequency, and exhibiting substantially symmetrical gain changes at frequencies below and above said fourth cutoff frequency.

35

12. An electric filter comprising a

plurality of notch filters combined so as to have a predetermined notch filter characteristic, the notch filters having different frequency characteristics.

5

13. The electric filter as claimed in claim 12, wherein said notch filters include:

10 a first notch filter having a first cutoff frequency and exhibiting substantially symmetrical gain changes at frequencies below and above said first cutoff frequency;

15 a second notch filter having a second cutoff frequency lower than said first cutoff frequency, and exhibiting a smaller amount of gain changes and a smaller maximum gain at frequencies below said second cutoff frequency than an amount of gain changes and a maximum gain at frequencies above  
20 said second cutoff frequency; and

a third notch filter having a third cutoff frequency higher than said first cutoff frequency, and exhibiting a larger amount of gain changes and a larger maximum gain at frequencies below said third  
25 cutoff frequency than an amount of gain changes and a maximum gain at frequencies above said third cutoff frequency.

30

14. The electric filter as claimed in claim 13, wherein said notch filters further include  
35 a fourth notch filter having a fourth cutoff frequency lower than said second cutoff frequency, and exhibiting substantially symmetrical gain changes at frequencies below and above said fourth

cutoff frequency.